



Notes:

1. Electrical:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
- ⓑ - Connector Operating Temperature: -40° C to +85° C
2. Materials and Finish:
 - M28 Coupling Ring: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
 - Plug Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
 - Interfacial Seal: Silicone, Color: White
 - Cable Gland: PA (Black) or Brass, Nickel Plated
 - Cable Gland Seal: NBR, Color: Black
 - Cable Gland Insert (Metal Version): Nylon, Color: White
 - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
- ⓒ - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
 - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
 - RJ45 Modular Boot: PVC, Color: Black
3. RoHS compliant

Directive 2002/95/EC RoHS Compliant

L	Part Number	
	Plastic Version with Unshielded Cable	Metallized Plastic Version with Shielded Cable
2 M	17-100574	17-100604
4 M	17-100584	17-100614
5 M	17-100594	17-100624

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance: Unless otherwise specified			Scale: 1.8:1	Dim. in
	Name	Title	Approval Date	Dimensional:	Angles:		Material: See Notes	
				2008	Date	Name	Title: RJ45 Cat. 5e Ethernet Patch Cords Strain Relief to Standard RoHS Compliant	
				Draw.	Jan. 22	Vincent Ke		
				Appd.	Jan. 22	J. Chaudry		
					Norm		Drawing No.: 39K1A378	
c		Jul/06/2011	Vincent Ke	D-old		DIN A3		
b		Feb/18/2009	Vincent Ke			Sheet 1/1		
a	original					Part No.: SEE P/N TABLE		
Rev.	Changes	Date	Name					